



CVE Shop **Glass Flex** is ideal for low to high pressure air conditioning and ventilation systems. Suitable for use in general ventilation applications including fresh air intake and exhaust, and kitchen and bathroom.

The standard grey coloured flex is constructed from reinforced glass fibre fabric encapsulating a high tensile wire helix.

Technical Data	
Diameter Range	80mm to 610mm
Temperature Range	-20°C to +110°C
Air Velocity	
Working Pressure	Maximum 2000 Pa positive
Colour	Grey
Standard Length	6 Metres

## Packaging

Unboxed.

## Installation ??????

Fully extend ducting, then cut to exact length using a sharp knife and pliers/wire cutters (see length calculations below). To fix insulated flex to spigots we recommend the Combi-Vent Flexi-Clip.

When installing flex, securely clamp the inner core first and then tape or clamp the outer jacket and inner core to the spigot. Taping the outer jacket to the spigot will prevent any fibre migration.

Sizes Available / Dimensions													
CVE Product Code	CVGF-100	CVGF-125	CVGF-150	CVGF-200	CVGF-250	CVGF-300	CVGF-315	CVGF-355	CVGF-400	CVGF-450	CVGF-500	CVGF-560	CVGF-610
Diameter	100mm	125mm	150mm	200mm	250mm	300mm	315mm	355mm	400mm	450mm	500mm	560mm	610mm
Length	6m	6m	6m	6m	6m	6m	6m	6m	6m	6m	6m	6m	6m

