



CVE Shop **Non Insulated Flexible Ducting** is ideal for ventilation, air conditioning, and air handling systems where a high mechanical strength and temperature is required.

This fully flexible laminate duct has a steel spiral inserted between the layers of the duct.

All our flexible duct products are easy to install, either on circular or oval connection parts.

Technical Data	
Diameter Range	100mm to 400mm
Temperature Range	-20°C to +80°C
Air Velocity	30 M/S maximum
Working Pressure	Maximum 2000 Pa positive
Colour	Metallic Silver
Standard Length	10 Metres

Packaging

Each 10 metre length is individually cartooned. This production and packaging configuration ensures that wastage through scrap is kept to a minimum and dramatically reduces the chance of damage in transit or on site.

Installation

Fully extend ducting, then cut to exact length using a sharp knife and pliers/wire cutters (see length calculations below). To fix insulated flex to spigots we recommend the Combi-Vent Flexi-Clip (one at each end).

Sizes Available / Dimensions									
CVE Product Code	CVALF-100	CVALF-125	CVALF-150	CVALF-200	CVALF-250	CVALF-300	CVALF-315	CVALF-355	CVALF-400
Diameter	100mm	125mm	150mm	200mm	250mm	300mm	315mm	355mm	400mm
Length	10m	10m	10m	10m	10m	10m	10m	10m	10m

